



#113: E-LINE 2-PLY HEAVY COVER GREEN PVC MONO AS CONVEYOR BELT

General conveying, horticultural, potato processing, material handling

PLIES: 2 | TOP COVER: DARK GREEN SMOOTH PVC | BOTTOM COVER:
FABRIC



[Request a Quote](#)



[Request a Sample](#)

Tags: [General Conveying](#), [Horticultural](#), [Material Handling](#), [Potato Processing](#), [Roller Applications](#)

TECHNICAL DATA

BELT THICKNESS:	3.0 mm	0.12"
PULLEY DIAMETER (MIN.):	50 mm	1.97"
PULLEY DIAMETER (MIN.) BACK FLEXING:	80 mm	3.15"
BELT WEIGHT:	3.3 kg/m ²	0.68 lb/ft ²
PRODUCTION WIDTH:	2000 or 3000 mm	78.75 or 118"
BREAKING STRENGTH:	150 N/mm	857 lbs/in
TENSION FOR 1% ELONGATION:	8 N/mm	46 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):	15 N/mm	86 lbs/in
OPERATING TEMPERATURE:	-15° to 80° C	5° to 176° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Smooth
PROPERTY:	1.2mm 80 A
COLOR:	Dark Green
BOTTOM COVER MATERIAL:	Fabric
SURFACE FINISH:	Smooth
COLOR:	

BELT FABRIC

TOP PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
INNER PLIES:	
BOTTOM PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
TOTAL NO. OF PLIES	2

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static	✓	
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable		✗
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗