



# #119: E-LINE 2-PLY PVC SLIP TOP CONVEYOR BELT

General conveying, accumulation. Diverting.

PLIES: 2 | TOP COVER: BLACK SLIP TOP PVC IMPREGNATED | BOTTOM COVER: WHITE LOW NOISE FABRIC



[Request a Quote](#)



[Request a Sample](#)

**Tags:** [Accumulation](#), [Diverting](#), [General Conveying](#), [Roller Applications](#)

## TECHNICAL DATA

BELT THICKNESS:	2.4 mm	0.94"
PULLEY DIAMETER (MIN.):	60 mm	2.36"
PULLEY DIAMETER (MIN.)	60 mm	2.36"
BACK FLEXING:	60 mm	2.36"
BELT WEIGHT:	1.4 kg/m <sup>2</sup>	0.29 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	3000 mm	118.11"
BREAKING STRENGTH:	160 N/mm	914 lbs/in
TENSION FOR 1% ELONGATION:	10 N/mm	57 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):	18 N/mm	103 lbs/in
OPERATING TEMPERATURE:	-10° to 90° C	14° to 194° F

## BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC Impregnated
SURFACE FINISH:	Slip Top
PROPERTY:	
COLOR:	Black
BOTTOM COVER MATERIAL:	Low Noise Fabric
SURFACE FINISH:	
COLOR:	White

## BELT FABRIC

TOP PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
INNER PLIES:	
BOTTOM PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
TOTAL NO. OF PLIES	2

## BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise	✓	
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗