



#119: E-LINE 2-PLY PVC SLIP TOP CONVEYOR BELT

General conveying, accumulation. Diverting.

PLIES: 2 | TOP COVER: BLACK SLIP TOP PVC IMPREGNATED | BOTTOM COVER: WHITE LOW NOISE FABRIC



[Request a Quote](#)



[Request a Sample](#)

Tags: [Accumulation](#), [Diverting](#), [General Conveying](#), [Roller Applications](#)

TECHNICAL DATA

| | | |
|---|-----------------------|-------------------------|
| BELT THICKNESS: | 2.4 mm | 0.94" |
| PULLEY DIAMETER (MIN.): | 60 mm | 2.36" |
| PULLEY DIAMETER (MIN.) | 60 mm | 2.36" |
| BACK FLEXING: | 60 mm | 2.36" |
| BELT WEIGHT: | 1.4 kg/m ² | 0.29 lb/ft ² |
| PRODUCTION WIDTH: | 3000 mm | 118.11" |
| BREAKING STRENGTH: | 160 N/mm | 914 lbs/in |
| TENSION FOR 1% ELONGATION: | 10 N/mm | 57 lbs/in |
| MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH): | 18 N/mm | 103 lbs/in |
| OPERATING TEMPERATURE: | -10° to 90° C | 14° to 194° F |

BELT CONSTRUCTION

| | |
|------------------------|------------------|
| TOP MATERIAL COVER: | PVC Impregnated |
| SURFACE FINISH: | Slip Top |
| PROPERTY: | |
| COLOR: | Black |
| BOTTOM COVER MATERIAL: | Low Noise Fabric |
| SURFACE FINISH: | |
| COLOR: | White |

BELT FABRIC

| | |
|--------------------|---|
| TOP PLY: | POLYESTER MONOFILAMENT WITH LATERAL STABILITY |
| INNER PLIES: | |
| BOTTOM PLY: | POLYESTER MONOFILAMENT WITH LATERAL STABILITY |
| TOTAL NO. OF PLIES | 2 |

BELT CHARACTERISTICS

| | YES | NO |
|-------------------------------|-----|----|
| Permanently Anti-Static | | ✗ |
| Nosebar Suitable | | ✗ |
| Powerturn Suitable | | ✗ |
| Slider Bed Suitable | ✓ | |
| Troughed Application Suitable | ✓ | |
| FDA / USDA Approved | | ✗ |
| Low Noise | ✓ | |
| Flame Retardant | | ✗ |
| Suitable for Metal Detector | | ✗ |
| Abrasion Resistant | | ✗ |