


[Request a Quote](#)

[Request a Sample](#)

#125: PVC 150 BLACK CRESCENT TOP CONVEYOR BELT

Aggressive scoop pattern for high incline conveying. Crescent pattern creates hundreds of tiny “buckets” capable of conveying liquids along with solids. Conversely, the belt can be run in the opposite direction, and the upside-down crescents convey solids while draining off liquids. Belt operates smoothly and quietly on return. Good tubeveyor belt.

PLIES: 1 | TOP COVER: BLACK CRESCENT PVC | BOTTOM COVER: BLACK INTERWOVEN FABRIC

Tags: [Bulk Product Conveying](#), [Fruits](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Industrial](#), [Material Handling](#), [Packaging](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#), [Vegetable Oil](#), [Vegetable Products](#)

TECHNICAL DATA

BELT THICKNESS:	6.6 mm	0.26"
PULLEY DIAMETER (MIN.):	76.2 mm	3"
PULLEY DIAMETER (MIN.) BACK FLEXING:	mm	"
BELT WEIGHT:	kg/m ²	0.09 lb/ft ²
PRODUCTION WIDTH:	1829 mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		150 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-18° to 82° C	0° to 180° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Crescent
PROPERTY:	
COLOR:	Black
BOTTOM COVER MATERIAL:	Interwoven Fabric
SURFACE FINISH:	Brushed
COLOR:	Black

BELT FABRIC

TOP PLY:	UNIPLY INTERWOVEN
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗