


[Request a Quote](#)

[Request a Sample](#)

#126: INTERWOVEN 150 BLUE COS LOW TEMP CONVEYOR BELT

FDA, Oil resistant, Good abrasion resistance, Good cut resistance, Low Temp Belt, 30% Nitrile rubber cover.

PLIES: 1 | TOP COVER: BLUE SMOOTH | BOTTOM COVER: INTERWOVEN FABRIC

Tags: [Abrasion Resistant](#), [Fruits](#), [General Conveying](#), [Horticultural](#), [Low Temperature](#), [Troughed Applications](#), [Turn Applications](#), [USDA / FDA](#), [Vegetable Oil](#), [Vegetable Products](#)

TECHNICAL DATA

BELT THICKNESS: 4 mm 0.157"

PULLEY DIAMETER (MIN.): 51 mm 2"

PULLEY DIAMETER (MIN.) 102 mm 4"

BACK FLEXING:

BELT WEIGHT: kg/m² 1.008 lb/ft²

PRODUCTION WIDTH: 1829 mm 72"

BREAKING STRENGTH:

TENSION FOR 1% ELONGATION: 150 lbs/in

MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):

OPERATING TEMPERATURE: -28° to 65° C -20° to 150° F

BELT CONSTRUCTION

TOP MATERIAL COVER:

SURFACE FINISH: Smooth

PROPERTY:

COLOR: Blue

BOTTOM COVER MATERIAL: Interwoven Fabric

SURFACE FINISH: Brushed

COLOR:

BELT FABRIC

TOP PLY: UNIPLY INTERWOVEN

INNER PLIES:

BOTTOM PLY:

TOTAL NO. OF PLIES 1

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗