



#126: INTERWOVEN 150 BLUE COS LOW TEMP CONVEYOR BELT

FDA, Oil resistant, Good abrasion resistance, Good cut resistance, Low Temp Belt, 30% Nitrile rubber cover.

PLIES: 1 | TOP COVER: BLUE SMOOTH | BOTTOM COVER: INTERWOVEN FABRIC



[Request a Quote](#)



[Request a Sample](#)

Tags: [Abrasion Resistant](#), [Fruits](#), [General Conveying](#), [Horticultural](#), [Low Temperature](#), [Troughed Applications](#), [Turn Applications](#), [USDA / FDA](#), [Vegetable Oil](#), [Vegetable Products](#)

TECHNICAL DATA

BELT THICKNESS:	4 mm	0.157"
PULLEY DIAMETER (MIN.):	51 mm	2"
PULLEY DIAMETER (MIN.)	102 mm	4"
BACK FLEXING:		
BELT WEIGHT:	kg/m ²	1.008 lb/ft ²
PRODUCTION WIDTH:	1829 mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		150 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-28° to 65° C	-20° to 150° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	
SURFACE FINISH:	Smooth
PROPERTY:	
COLOR:	Blue
BOTTOM COVER MATERIAL:	Interwoven Fabric
SURFACE FINISH:	Brushed
COLOR:	

BELT FABRIC

TOP PLY:	UNIPLY INTERWOVEN
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗