



#127: INTERWOVEN 150 BLUE CRESCENT TOP LOW TEMP CONVEYOR BELT



[Request a Quote](#)

Crescent top cover, Brushed pulley side, Low temp rated, Super oil and grease resistance, High abrasion resistance, FDA.

PLIES: 1 | TOP COVER: BLUE CRESCENT | BOTTOM COVER: INTERWOVEN FABRIC

Tags: [Fruits](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Troughed Applications](#), [USDA / FDA](#), [Vegetable Oil](#), [Vegetable Products](#)

TECHNICAL DATA

BELT THICKNESS:	6.5 mm	.256"
PULLEY DIAMETER (MIN.):	102 mm	4"
PULLEY DIAMETER (MIN.) BACK FLEXING:	153 mm	6"
BELT WEIGHT:	5.2 kg/m ²	lb/ft ²
PRODUCTION WIDTH:	1829	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		150 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-28° to 65° C	-20° to 150° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	
SURFACE FINISH:	Crescent
PROPERTY:	
COLOR:	Blue
BOTTOM COVER MATERIAL:	Interwoven Fabric
SURFACE FINISH:	Brushed
COLOR:	

BELT FABRIC

TOP PLY:	UNIPLY INTERWOVEN
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant	✓	