



#127: INTERWOVEN 150 BLUE CRESCENT TOP LOW TEMP CONVEYOR BELT


[Request a Quote](#)

[Request a Sample](#)

Crescent top cover, Brushed pulley side, Low temp rated, Super oil and grease resistance, High abrasion resistance, FDA.

PLIES: 1 | TOP COVER: BLUE CRESCENT | BOTTOM COVER: INTERWOVEN FABRIC

Tags: [Fruits](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Troughed Applications](#), [USDA / FDA](#), [Vegetable Oil](#), [Vegetable Products](#)

TECHNICAL DATA

BELT THICKNESS: 6.5 mm .256"

PULLEY DIAMETER (MIN.): 102 mm 4"

PULLEY DIAMETER (MIN.) 153 mm 6"

BACK FLEXING:

BELT WEIGHT: 5.2 kg/m² lb/ft²

PRODUCTION WIDTH: 1829 72"

BREAKING STRENGTH:

TENSION FOR 1% ELONGATION: 150 lbs/in

MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):

OPERATING TEMPERATURE: -28° to 65° C -20° to 150° F

BELT CONSTRUCTION

TOP MATERIAL COVER:

SURFACE FINISH: Crescent

PROPERTY:

COLOR: Blue

BOTTOM COVER MATERIAL: Interwoven Fabric

SURFACE FINISH: Brushed

COLOR:

BELT FABRIC

TOP PLY: UNIPLY INTERWOVEN

INNER PLIES:

BOTTOM PLY:

TOTAL NO. OF PLIES 1

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant	✓	