



#128: E-LINE ET120RT-W ROUGH TOP CONVEYOR BELT

PLIES: 1 | TOP COVER: PVC 50 A | BOTTOM COVER: POLYESTER



[Request a Quote](#)



[Request a Sample](#)

Tags: [Abrasion Resistant](#), [Animal Fats](#), [Bulk Product Conveying](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Industrial](#), [Material Handling](#), [Metal Parts](#), [Mineral Oil](#), [Packaging](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#), [Vegetable Oil](#), [Vegetable Products](#)

TECHNICAL DATA

BELT THICKNESS:	5.50 mm	0.2165"
PULLEY DIAMETER (MIN.):	58 mm	2.3"
PULLEY DIAMETER (MIN.) BACK FLEXING:	81 mm	3.2"
BELT WEIGHT:	kg/m ²	lb/ft ²
PRODUCTION WIDTH:	mm	"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	25 N/mm	143 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-18° to 82° C	0° to 180° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC 50 A
SURFACE FINISH:	Rough Top
PROPERTY:	Flexible
COLOR:	White
BOTTOM COVER MATERIAL:	
SURFACE FINISH:	
COLOR:	

BELT FABRIC

TOP PLY:	PVC 50 A
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector	✓	
Abrasion Resistant		✗