



## #130: 2-PLY GRAY PVC MONO WAVY ROUGH TOP AS CONVEYOR BELT

General conveying, incline, material handling, distribution centers, packaging.

PLIES: 2 | TOP COVER: GRAY ROUGH TOP PVC | BOTTOM COVER: FABRIC


[Request a Quote](#)

[Request a Sample](#)

**Tags:** [Distribution Centers](#), [General Conveying](#), [Incline](#), [Material Handling](#), [Packaging](#)

### TECHNICAL DATA

BELT THICKNESS:	5.3 mm	0.209"
PULLEY DIAMETER (MIN.):	80 mm	3.15"
PULLEY DIAMETER (MIN.)	120 mm	4.72"
BACK FLEXING:		
BELT WEIGHT:	4.5 kg/m <sup>2</sup>	0.92 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	2000 mm	78.74"
BREAKING STRENGTH:	180 N/mm	1,027 lbs/in
TENSION FOR 1% ELONGATION:	10 N/mm	57 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):	18 N/mm	103 lbs/in
OPERATING TEMPERATURE:	-20° to 70° C	-4° to 158° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Rough Top
PROPERTY:	3.5mm 55 A
COLOR:	Gray
BOTTOM COVER MATERIAL:	Fabric
SURFACE FINISH:	Smooth
COLOR:	

### BELT FABRIC

TOP PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
INNER PLIES:	
BOTTOM PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
TOTAL NO. OF PLIES	2

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static	✓	
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable		✗
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗