



## #19: 3-PLY HOT STOCK & WATER

Bare duck surface down for lowest possible friction for slider bed use, and up for deflector bar applications; ideal as slip-top belt for “stall” operations. Its true designed use is for conveying uncured rubber in tire plants with the cotton surface saturated with water.



[Request a Quote](#)

PLIES: 3 | TOP COVER: WHITE BARE DUCK | BOTTOM COVER: FRICTION FABRIC

**Tags:** [Accumulation](#), [Airports](#), [General Conveying](#), [Industrial](#), [Material Handling](#), [Plastics](#), [Troughed Applications](#), [Turn Applications](#)

### TECHNICAL DATA

BELT THICKNESS:	3.556 mm	0.14"
PULLEY DIAMETER (MIN.):	63.5 mm	2.5"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m <sup>2</sup>	0.061 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		90 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-40° to 121° C	-40° to 250° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	Bare Duck
SURFACE FINISH:	
PROPERTY:	
COLOR:	White
BOTTOM COVER MATERIAL:	Friction Fabric
SURFACE FINISH:	
COLOR:	

### BELT FABRIC

TOP PLY:	POLYESTER / COTTON
INNER PLIES:	POLYESTER / COTTON
BOTTOM PLY:	POLYESTER / COTTON
TOTAL NO. OF PLIES	3

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗