


[Request a Quote](#)

[Request a Sample](#)

## 2-PLY BLUE WAVE PVC MONO

### General Characteristics:

- 2 cross rigid carcass
- 60Shore A light blue top cover
- Blue berry wave embossed

FDA

PLIES: 2 | TOP COVER: BB EMBOSSED | BOTTOM COVER: POLYESTER

**Tags:** [Abrasion Resistant](#), [Animal Fats](#), [Bulk Product Conveying](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Industrial](#), [Material Handling](#), [Metal Parts](#), [Mineral Oil](#), [Packaging](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#), [Vegetable Oil](#), [Vegetable Products](#)

### TECHNICAL DATA

BELT THICKNESS:	7.5 mm	0.2953"
PULLEY DIAMETER (MIN.):	75 mm	3"
PULLEY DIAMETER (MIN.)	150 mm	6"
BACK FLEXING:		
BELT WEIGHT:	2.4 kg/m <sup>2</sup>	.491 lb/ft <sup>2</sup>
PRODUCTION WIDTH:		
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	10 N/mm	
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-17° to 60° C	0° to 140° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	BB Embossed
SURFACE FINISH:	
PROPERTY:	Rigid
COLOR:	Blue
BOTTOM COVER MATERIAL:	Polyester
SURFACE FINISH:	
COLOR:	

### BELT FABRIC

TOP PLY:	BB EMBOSSED
INNER PLIES:	
BOTTOM PLY:	POLYESTER
TOTAL NO. OF PLIES	2

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable		✗
Troughed Application Suitable		✗
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗