



## #23: NOVBELT 600 NA GREEN

Wear and cut resistant, soft impact surface, high temperature resistant, quiet running.

PLIES: 1 | TOP COVER: GREEN NON-WOVEN NBR IMPREGNATED POLYESTER | BOTTOM COVER: GREEN NON-WOVEN IMPREGNATED POLYESTER



[Request a Quote](#)



[Request a Sample](#)

**Tags:** [Abrasion Resistant](#), [Accumulation](#), [Airports](#), [Distribution Centers](#), [Diverting](#), [General Conveying](#), [Horticultural](#), [Industrial](#), [Material Handling](#), [Metal Parts](#), [Mineral Oil](#), [Nuts and Seeds](#), [Packaging](#), [Troughed Applications](#), [Turn Applications](#)

### TECHNICAL DATA

BELT THICKNESS:	5.65 mm	0.223"
PULLEY DIAMETER (MIN.):	100 mm	4"
PULLEY DIAMETER (MIN.) BACK FLEXING:	200 mm	7.87"
BELT WEIGHT:	kg/m <sup>2</sup>	.064 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	2000mm	78.74"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	12 N/mm	
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-10° to 120° C	-4° to 248° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	NBR Impregnated Polyester
SURFACE FINISH:	Non-Woven
PROPERTY:	
COLOR:	Green
BOTTOM COVER MATERIAL:	Non-Woven Impregnated Polyester
SURFACE FINISH:	
COLOR:	Green

### BELT FABRIC

TOP PLY:	NON-WOVEN PLY
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise	✓	
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant	✓	