


[Request a Quote](#)

[Request a Sample](#)

#24: NOVBELT 250 NA WHITE

Wear and cut resistant, soft impact surface, high temperature resistant, quiet running. MAIN APPLICATIONS: Food grade belts; dough sheeters, bakery, flour duster, pizza conveying, transfer and cutting or puffed dough. Metal, Mechanical and Automotive industries: Sheet and bodies conveying, assembly system; Mail & post sorting equipments, Airport & Railway luggage handling: Packages and luggage sorting; Industrial laundries, Packing lines.

PLIES: 1 | TOP COVER: WHITE NON-WOVEN NBR IMPREGNATED POLYESTER | BOTTOM COVER: WHITE NON-WOVEN IMPREGNATED POLYESTER

Tags: [Abrasion Resistant](#), [Airports](#), [Distribution Centers](#), [General Conveying](#), [Hi-Temp](#), [Horticultural](#), [Industrial](#), [Material Handling](#), [Metal Parts](#), [Mineral Oil](#), [Nuts and Seeds](#), [Packaging](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#), [Unpackaged Food](#), [USDA / FDA](#), [Vegetable Oil](#), [Vegetable Products](#)

TECHNICAL DATA

BELT THICKNESS:	2.5 mm	.009"
PULLEY DIAMETER (MIN.):	30 mm	1.18"
PULLEY DIAMETER (MIN.) BACK FLEXING:	60 mm	2.36"
BELT WEIGHT:	kg/m ²	.024 lb/ft ²
PRODUCTION WIDTH:	2000 mm	78.74"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	8 N/mm	
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-10° to 120° C	-4° to 248° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	NBR Impregnated Polyester
SURFACE FINISH:	Non-Woven
PROPERTY:	
COLOR:	White
BOTTOM COVER MATERIAL:	Non-Woven Impregnated Polyester
SURFACE FINISH:	
COLOR:	White

BELT FABRIC

TOP PLY:	NON-WOVEN PLY
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved	✓	
Low Noise	✓	
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant	✓	