



#29: DARK GRAY PVC LATTICE TOP CONVEYOR BELT


[Request a Quote](#)

[Request a Sample](#)

Decline belt, incline belt, incline belt, sorting belt, transfer belt.

Distribution centers, materials handling, postal / mail / parcel sorting.

Various industries. Constant and gentle positive grip. Low noise running / pulley side.

PLIES: 2 | TOP COVER: DARK GRAY LATTICE TOP PVC | BOTTOM COVER:

Tags: [Distribution Centers](#), [General Conveying](#), [Industrial](#), [Material Handling](#), [Packaging](#)

TECHNICAL DATA

BELT THICKNESS:	2.032 mm	0.08"
PULLEY DIAMETER (MIN.):	50.8 mm	2"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m ²	0.49 lb/ft ²
PRODUCTION WIDTH:	3200 mm	126"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	8 N/mm	
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	14° to 60° C	-10° to 140° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Lattice Top
PROPERTY:	
COLOR:	Dark Gray
BOTTOM COVER MATERIAL:	Monofilament Fabric
SURFACE FINISH:	
COLOR:	

BELT FABRIC

TOP PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
INNER PLIES:	
BOTTOM PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
TOTAL NO. OF PLIES	2

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static	✓	
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable		✗
FDA / USDA Approved		✗
Low Noise	✓	
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗