



## #30: 2-PLY GRAY PVC SNAKESKIN CONVEYOR BELT

Features a low durometer PVC compound with a snakeskin impression on a 2 ply monofilament carcass. This belt will provide a positive (sticky) carrying surface. The carcass will permit this belt to travel at high speeds with low noise. Can be used in package handling, manufacturing, post office applications. It is a high traction belt for moderate inclines.

PLIES: 2 | TOP COVER: GRAY SNAKESKIN PATTERN | BOTTOM COVER: MONOFILAMENT FABRIC


[Request a Quote](#)

[Request a Sample](#)

**Tags:** [General Conveying](#), [Incline](#), [Material Handling](#), [Packaging](#), [Paper Processing](#)

### TECHNICAL DATA

BELT THICKNESS:	2.2 mm	0.087"
PULLEY DIAMETER (MIN.):	51 mm	2"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m <sup>2</sup>	0.51 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	mm	78"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	8 N/mm	
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		

OPERATING TEMPERATURE: -10° to 70° C      14° to 158° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	
SURFACE FINISH:	Snakeskin Pattern
PROPERTY:	
COLOR:	Gray
BOTTOM COVER MATERIAL:	Monofilament Fabric
SURFACE FINISH:	
COLOR:	

### BELT FABRIC

TOP PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
INNER PLIES:	
BOTTOM PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY
TOTAL NO. OF PLIES	2

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static	✓	
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable		✗
FDA / USDA Approved		✗
Low Noise	✓	
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗