



# #38: PVC 120 CBS BLACK CONVEYOR BELT

Has proven to be the longest wearing, best performing, most problem free package handling belt available today. Economical, general purpose specifications ideal for a variety of roller bed, and live roller applications. Offer low stretch, high fastener holding ability and superior rip, tear, and gouge resistance.



[Request a Quote](#)



[Request a Sample](#)

PLIES: 1 | TOP COVER: BLACK SMOOTH PVC | BOTTOM COVER: BLACK PVC

**Tags:** [General Conveying](#), [Horticultural](#), [Industrial](#), [Material Handling](#), [Packaging](#)

## TECHNICAL DATA

BELT THICKNESS:	3.97 mm	0.15625"
PULLEY DIAMETER (MIN.):	63.5 mm	2.5"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m <sup>2</sup>	0.90 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	1829 mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		120 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-18° to 82° C	0° to 180° F

## BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Smooth
PROPERTY:	
COLOR:	Black
BOTTOM COVER MATERIAL:	PVC
SURFACE FINISH:	Smooth
COLOR:	Black

## BELT FABRIC

TOP PLY:	UNIPLY INTERWOVEN
INNER PLYS:	
BOTTOM PLY:	
TOTAL NO. OF PLYS	1

## BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable		✗
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗