


[Request a Quote](#)

[Request a Sample](#)

## #39: PVC 150 FBS BLACK CONVEYOR BELT

An economical interwoven all-polyester belt impregnated with PVC. Low-stretch construction and brushed-friction slider-bed back make this belt a good choice for general conveying of boxes, parts, and other light unit loads where a protective belt cover is not needed.

PLIES: 1 | TOP COVER: BLACK FRICTION PVC | BOTTOM COVER: BLACK INTERWOVEN FABRIC

**Tags:** [Fruits](#), [General Conveying](#), [Horticultural](#), [Industrial](#), [Material Handling](#), [Packaging](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#)

### TECHNICAL DATA

BELT THICKNESS:	3.81 mm	0.15"
PULLEY DIAMETER (MIN.):	76.2 mm	3"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m <sup>2</sup>	0.72 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		150 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-18° to 82° C	0° to 180° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Friction
PROPERTY:	
COLOR:	Black
BOTTOM COVER MATERIAL:	Interwoven Fabric
SURFACE FINISH:	Brushed
COLOR:	Black

### BELT FABRIC

TOP PLY:	UNIPLY INTERWOVEN
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗