


[Request a Quote](#)

[Request a Sample](#)

## #44: PVC 200 CBS BLACK CONVEYOR BELT

This versatile, 200 PIW belt offers excellent service in grain elevator legs. The all-polyester carcass provides good bolt holding, low-stretch and excellent fastener retention. Also popular as a heavy duty package and bulk product conveying belt.

PLIES: 1 | TOP COVER: BLACK SMOOTH PVC | BOTTOM COVER: BLACK PVC

**Tags:** [Bulk Product Conveying](#), [Fruits](#), [General Conveying](#), [Horticultural](#), [Industrial](#), [Material Handling](#), [Packaging](#), [Potato Processing](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#), [Vegetable Oil](#), [Vegetable Products](#)

### TECHNICAL DATA

BELT THICKNESS:	5.969 mm	0.235"
PULLEY DIAMETER (MIN.):	127 mm	5"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m <sup>2</sup>	1.51 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	mm	"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		200 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-18° to 82° C	0° to 180° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Smooth
PROPERTY:	
COLOR:	Black
BOTTOM COVER MATERIAL:	PVC
SURFACE FINISH:	Smooth
COLOR:	Black

### BELT FABRIC

TOP PLY:	UNIPLY INTERWOVEN
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable		✗
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗