



#53: 3-PLY TAN PURE GUM ROUGH TOP CONVEYOR BELT



[Request a Quote](#)



[Request a Sample](#)

Genuine gum with soft durometer fight highest grab, steepest inclines, abrasion resistance and long wear. Very resistant to cutting and gouging. Flexible, very high-strength RFL treated polyester/nylon fabric, which offers reduced edge fray and superior fastener holding. NON MARKING

PLIES: 3 | TOP COVER: TAN ROUGH TOP PURE GUM RUBBER | BOTTOM COVER: BARE RFL FABRIC

Tags: [Abrasion Resistant](#), [Bulk Product Conveying](#), [General Conveying](#), [Horticultural](#), [Industrial](#), [Material Handling](#), [Packaging](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#)

TECHNICAL DATA

BELT THICKNESS:	7.24 mm	0.285"
PULLEY DIAMETER (MIN.):	76 mm	3"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m ²	1.2 lb/ft ²
PRODUCTION WIDTH:	mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		150 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-29° to 121° C	-20° to 250° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	Pure Gum Rubber
SURFACE FINISH:	Rough Top
PROPERTY:	
COLOR:	Tan
BOTTOM COVER MATERIAL:	Bare RFL Fabric
SURFACE FINISH:	
COLOR:	

BELT FABRIC

TOP PLY:	POLYESTER / NYLON
INNER PLIES:	POLYESTER / NYLON
BOTTOM PLY:	POLYESTER / NYLON
TOTAL NO. OF PLIES	3

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant	✓	