


[Request a Quote](#)

[Request a Sample](#)

#53: 3-PLY TAN PURE GUM ROUGH TOP CONVEYOR BELT

Genuine gum with soft durometer fight highest grab, steepest inclines, abrasion resistance and long wear. Very resistant to cutting and gouging. Flexible, very high-strength RFL treated polyester/nylon fabric, which offers reduced edge fray and superior fastener holding. NON MARKING

PLIES: 3 | TOP COVER: TAN ROUGH TOP PURE GUM RUBBER | BOTTOM COVER: BARE RFL FABRIC

Tags: [Abrasion Resistant](#), [Bulk Product Conveying](#), [General Conveying](#), [Horticultural](#), [Industrial](#), [Material Handling](#), [Packaging](#), [Recycling](#), [Troughed Applications](#), [Turn Applications](#)

TECHNICAL DATA

BELT THICKNESS:	7.24 mm	0.285"
PULLEY DIAMETER (MIN.):	76 mm	3"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m ²	1.2 lb/ft ²
PRODUCTION WIDTH:	mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		150 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-29° to 121° C	-20° to 250° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	Pure Gum Rubber
SURFACE FINISH:	Rough Top
PROPERTY:	
COLOR:	Tan
BOTTOM COVER MATERIAL:	Bare RFL Fabric
SURFACE FINISH:	
COLOR:	

BELT FABRIC

TOP PLY:	POLYESTER / NYLON
INNER PLIES:	POLYESTER / NYLON
BOTTOM PLY:	POLYESTER / NYLON
TOTAL NO. OF PLIES	3

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable	✓	
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant	✓	