



# #59 2-PLY BLUE WAVE PVC MONO

General Characteristics:

- 2 ply cross rigid carcass
- 65Shore A light blue top cover
- Blue berry wave embossed

FDA

PLIES: 2 | TOP COVER: BB EMBOSSED | BOTTOM COVER: POLYESTER



[Request a Quote](#)



[Request a Sample](#)

**Tags:** [Animal Fats](#), [Bulk Product Conveying](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Industrial](#), [Material Handling](#), [Mineral Oil](#), [Packaging](#), [Recycling](#), [Vegetable Oil](#), [Vegetable Products](#)

## TECHNICAL DATA

BELT THICKNESS:	7 mm	0.2756"
PULLEY DIAMETER (MIN.):	102 mm	4"
PULLEY DIAMETER (MIN.)	127 mm	5"
BACK FLEXING:		
BELT WEIGHT:	4.3 kg/m <sup>2</sup>	.8807 lb/ft <sup>2</sup>
PRODUCTION WIDTH:		
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	8 N/mm	
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-18° to 71° C	0° to 160° F

## BELT CONSTRUCTION

TOP MATERIAL COVER:	BB Embossed
SURFACE FINISH:	
PROPERTY:	Rigid
COLOR:	Blue
BOTTOM COVER MATERIAL:	Polyester
SURFACE FINISH:	
COLOR:	

## BELT FABRIC

TOP PLY:	BB EMBOSSED
INNER PLIES:	
BOTTOM PLY:	POLYESTER
TOTAL NO. OF PLIES	2

## BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable		✗
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗