



#60: 3-PLY BLACK V-RIDGE CONVEYOR BELT

Cross corrugated peaks are equivalent to small cleats, will convey on high incline. M-Shaped ridges are soft, durable and self cleaning; used to convey cardboard cartons.



[Request a Quote](#)

PLIES: 3 | TOP COVER: BLACK | BOTTOM COVER:

Tags: [Bulk Product Conveying](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Industrial](#), [Material Handling](#), [Packaging](#), [Troughed Applications](#)

TECHNICAL DATA

BELT THICKNESS:	7.95 mm	0.313"
PULLEY DIAMETER (MIN.):	63.5 mm	2.5"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m ²	0.10 lb/ft ²
PRODUCTION WIDTH:	mm	72"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		90 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-40° to 121° C	-40° to 250° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	
SURFACE FINISH:	
PROPERTY:	
COLOR:	Black
BOTTOM COVER MATERIAL:	
SURFACE FINISH:	
COLOR:	

BELT FABRIC

TOP PLY:	POLYESTER SPUN
INNER PLIES:	POLYESTER SPUN
BOTTOM PLY:	POLYESTER SPUN
TOTAL NO. OF PLIES	3

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗