


[Request a Quote](#)

[Request a Sample](#)

#63: 3-PLY CP30 BLACK DURALIFT X FS

Long wearing, solid inverted V-shaped ridges prevent back sliding on high inclines. Self-cleaning belt is popular as case conveyor in bottling industry.

PLIES: 3 | TOP COVER: BLACK INVERTED V-RIBS SBR | BOTTOM COVER: FRICTION FABRIC

Tags: [Bulk Product Conveying](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Material Handling](#), [Packaging](#)

TECHNICAL DATA

BELT THICKNESS:	mm	"
PULLEY DIAMETER (MIN.):	76.2 mm	3"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	kg/m ²	lb/ft ²
PRODUCTION WIDTH:	mm	"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-40° to 121° C	-40° to 250° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	SBR
SURFACE FINISH:	1/4" Inverted V-Ribs
PROPERTY:	
COLOR:	Black
BOTTOM COVER MATERIAL:	Friction Fabric
SURFACE FINISH:	
COLOR:	

BELT FABRIC

TOP PLY:	COTTON POLYESTER
INNER PLIES:	COTTON POLYESTER
BOTTOM PLY:	COTTON POLYESTER
TOTAL NO. OF PLIES	3

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗