



# #74: XVT-2238 FOLDER GLUER BELT

Main Industry Segments: Paper converting; Box making/folder gluer; Paper manufacturing. Belt Applications: Folder-gluer belt. Special Features: Constant coefficient of friction; Constant grip and release property; Forgiving in case of short term shock like overloads. Mode of Use/Conveyance: Declined; Horizontal; Inclined; Twists with short center distance; Vertical



[Request a Quote](#)

PLIES: 2 | TOP COVER: GREEN ROUGH STRUCTURE NBR | BOTTOM COVER: DARK GREEN NBR

**Tags:** [Incline](#), [Paper Processing](#)

## TECHNICAL DATA

BELT THICKNESS:	4.0 mm	0.160"
PULLEY DIAMETER (MIN.):	40 mm	1.6"
PULLEY DIAMETER (MIN.) BACK FLEXING:	mm	"
BELT WEIGHT:	4.5 kg/m <sup>2</sup>	0.92 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	1200 mm	47"
		29 lbs/in

MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):

OPERATING TEMPERATURE:	0° to 60° C	32° to 140° F
------------------------	-------------	---------------

## BELT CONSTRUCTION

TOP MATERIAL COVER:	NBR
SURFACE FINISH:	Rough Structure
PROPERTY:	
COLOR:	Green
BOTTOM COVER MATERIAL:	NBR
	Rough Structure
COLOR:	Dark Green

## BELT FABRIC

TOP PLY:	POLYAMIDE (PA)
INNER PLIES:	
BOTTOM PLY:	POLYAMIDE (PA)
TOTAL NO. OF PLIES	2

## BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable		✗
Troughed Application Suitable		✗
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗