



#74A: XVT-2226 FOLDER GLUER BELT (CM-4/50F)



[Request a Quote](#)

Main Industry Segments: Paper converting; Box making/folder gluer; Paper manufacturing. Belt Applications: Folder-gluer belt. Special Features: Adhesive-free joint; Dimensionally stable; Longitudinal flexibility. Mode of Use/Conveyance: Declined; Horizontal; Inclined; Vertical.

PLIES: 2 | TOP COVER: GREEN ROUGH STRUCTURE NBR | BOTTOM COVER: DARK GREEN NBR

Tags: [Incline](#), [Paper Processing](#)

TECHNICAL DATA

| | | |
|---|-----------------------|-------------------------|
| BELT THICKNESS: | 5 mm | 0.200" |
| PULLEY DIAMETER (MIN.): | 50.8 mm | 2" |
| PULLEY DIAMETER (MIN.) BACK FLEXING: | mm | " |
| BELT WEIGHT: | 5.7 kg/m ² | 1.17 lb/ft ² |
| PRODUCTION WIDTH: | 1200 mm | 47" |
| BREAKING STRENGTH: | | |
| TENSION FOR 1% ELONGATION: | 7 N/mm | 40 lbs/in |
| MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH): | | |
| OPERATING TEMPERATURE: | -20° to 65° C | -4° to 149° F |

BELT CONSTRUCTION

| | |
|------------------------|-----------------|
| TOP MATERIAL COVER: | NBR |
| SURFACE FINISH: | Rough Structure |
| PROPERTY: | |
| COLOR: | Green |
| BOTTOM COVER MATERIAL: | NBR |
| | Rough Structure |
| COLOR: | Dark Green |

BELT FABRIC

| | |
|-----------------------|----------------|
| TOP PLY: | POLYAMIDE (PA) |
| INNER PLIES: | |
| BOTTOM PLY: | |
| TOTAL NO. OF PLIES | 2 |

BELT CHARACTERISTICS

| | YES | NO |
|-------------------------------|-----|----|
| Permanently Anti-Static | | X |
| Nosebar Suitable | | X |
| Powerturn Suitable | | X |
| Slider Bed Suitable | | X |
| Troughed Application Suitable | | X |
| FDA / USDA Approved | | X |
| Low Noise | | X |
| Flame Retardant | | X |
| Suitable for Metal Detector | | X |
| Abrasion Resistant | | X |