



Request a Quote

#74A: XVT-2226 FOLDER GLUER BELT

Main Industry Segments: Paper converting; Box making/folder gluer; Paper manufacturing. Belt Applications: Folder-gluer belt. Special Features: Adhesive-free joint; Dimensionally stable; Longitudinal flexibility. Mode of Use/Conveyance: Declined; Horizontal; Inclined; Vertical.

PLIES: 2 | TOP COVER: GREEN ROUGH STRUCTURE NBR | BOTTOM

COVER: DARK GREEN NBR

Tags: Incline, Paper Processing

TECHNICAL DATA

BELT THICKNESS:	5 mm	0.200"
PULLEY DIAMETER (MIN.):	50.8 mm	2"
PULLEY DIAMETER (MIN.) BACK FLEXING:	mm	п
BELT WEIGHT:	5.7 kg/m²	1.17 lb/ft²
PRODUCTION WIDTH:	1200 mm	47"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	7 N/mm	40 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-20° to 65° C	-4° to 149° F

BELT CONSTRUCTION

TOP MATERIAL COVER:

SURFACE FINISH:	Rough Structure
PROPERTY:	
COLOR:	Green
BOTTOM COVER MATERIAL:	NBR
	Rough Structure
COLOR:	Dark Green

NBR

BELT FABRIC

TOP PLY:	POLYAMIDE (PA)
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	2

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		×
Nosebar Suitable		×
Powerturn Suitable		×
Slider Bed Suitable		×
Troughed Application Suitable		×
FDA / USDA Approved		×
Low Noise		×
Flame Retardant		×
Suitable for Metal Detector		×
Abrasion Resistant		X