



# #75: XVT-2236 FOLDER GLUER BELT (FR-18/60)



[Request a Quote](#)

Main Industry Segments: Box making/folder gluer; Paper manufacturing.  
 Belt Applications: Folder-gluer belt; Tubewinder belt. Special Features: Constant coefficient of friction; Constant grip and release property; Forgiving in case of short term shock like overloads. Mode of Use/Conveyance: Declined; Horizontal; Inclined; Twists with short center distance; Vertical

PLIES: 2 | TOP COVER: GREEN ROUGH STRUCTURE NBR | BOTTOM COVER: DARK GREEN ROUGH STRUCTURE

**Tags:** [Incline](#), [Paper Processing](#)

## TECHNICAL DATA

BELT THICKNESS:	6.0 mm	0.240"
PULLEY DIAMETER (MIN.):	60 mm	2.4"
PULLEY DIAMETER (MIN.) BACK FLEXING:	mm	"
BELT WEIGHT:	7.1 kg/m <sup>2</sup>	1.45 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	1200 mm	47"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	7.5 N/mm	43 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	0° to 60° C	32° to 140° F

## BELT CONSTRUCTION

TOP MATERIAL COVER:	NBR
SURFACE FINISH:	Rough Structure
PROPERTY:	
COLOR:	Green
BOTTOM COVER MATERIAL:	Rough Structure
	Rough Structure
COLOR:	Dark Green

## BELT FABRIC

TOP PLY:	POLYAMIDE (PA)
INNER PLIES:	
BOTTOM PLY:	POLYAMIDE (PA)
TOTAL NO. OF PLIES	2

## BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		X
Nosebar Suitable		X
Powerturn Suitable		X
Slider Bed Suitable		X
Troughed Application Suitable		X
FDA / USDA Approved		X
Low Noise		X
Flame Retardant		X
Suitable for Metal Detector		X
Abrasion Resistant		X