


[Request a Quote](#)

[Request a Sample](#)

#75: XVT-2236 FOLDER GLUER BELT

Main Industry Segments: Box making/folder gluer; Paper manufacturing.
Belt Applications: Folder-gluer belt; Tubewinder belt. Special Features: Constant coefficient of friction; Constant grip and release property; Forgiving in case of short term shock like overloads. Mode of Use/Conveyance: Declined; Horizontal; Inclined; Twists with short center distance; Vertical

PLIES: 2 | TOP COVER: GREEN ROUGH STRUCTURE NBR | BOTTOM COVER: DARK GREEN ROUGH STRUCTURE

Tags: [Incline](#), [Paper Processing](#)

TECHNICAL DATA

| | | |
|---|-----------------------|-------------------------|
| BELT THICKNESS: | 6.0 mm | 0.240" |
| PULLEY DIAMETER (MIN.): | 60 mm | 2.4" |
| PULLEY DIAMETER (MIN.) | mm | " |
| BACK FLEXING: | | |
| BELT WEIGHT: | 7.1 kg/m ² | 1.45 lb/ft ² |
| PRODUCTION WIDTH: | 1200 mm | 47" |
| BREAKING STRENGTH: | | |
| TENSION FOR 1% ELONGATION: | 7.5 N/mm | 43 lbs/in |
| MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH): | | |
| OPERATING TEMPERATURE: | 0° to 60° C | 32° to 140° F |

BELT CONSTRUCTION

| | |
|------------------------|-----------------|
| TOP MATERIAL COVER: | NBR |
| SURFACE FINISH: | Rough Structure |
| PROPERTY: | |
| COLOR: | Green |
| BOTTOM COVER MATERIAL: | Rough Structure |
| | Rough Structure |
| COLOR: | Dark Green |

BELT FABRIC

| | |
|--------------------|----------------|
| TOP PLY: | POLYAMIDE (PA) |
| INNER PLIES: | |
| BOTTOM PLY: | POLYAMIDE (PA) |
| TOTAL NO. OF PLIES | 2 |

BELT CHARACTERISTICS

| | YES | NO |
|-------------------------------|-----|----|
| Permanently Anti-Static | | ✗ |
| Nosebar Suitable | | ✗ |
| Powerturn Suitable | | ✗ |
| Slider Bed Suitable | | ✗ |
| Troughed Application Suitable | | ✗ |
| FDA / USDA Approved | | ✗ |
| Low Noise | | ✗ |
| Flame Retardant | | ✗ |
| Suitable for Metal Detector | | ✗ |
| Abrasion Resistant | | ✗ |