



#76: XVT-2205 HABASIT BELTING (CM-4/30F)

Main Industry Segments: Cardboard converting, Paper manufacturing and processing. Belt Applications: Folder-gluer belt, Processing belt. Special Features: Abrasion resistant, Adhesive-free joint, Constant coefficient of friction, Dimensionally stable, Forgiving in case of short term shock like overloads.

PLIES: 2 | TOP COVER: GREEN ROUGH STRUCTURE NBR | BOTTOM COVER: LIGHT GREEN NBR



[Request a Quote](#)

Tags: [Cardboard Converting](#), [Paper Processing](#)

TECHNICAL DATA

BELT THICKNESS:	3 mm	0.12"
PULLEY DIAMETER (MIN.):	40 mm	1.57"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	3.2 kg/m ² 0.655	lb/ft ²
PRODUCTION WIDTH:	1140 mm	44.88"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	4 N/mm	23 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-20° to 65° C	-4° to 149° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	NBR
SURFACE FINISH:	Rough Structure
PROPERTY:	
COLOR:	Light Green
BOTTOM COVER MATERIAL:	NBR
	Rough Structure
COLOR:	Yellow

BELT FABRIC

TOP PLY:	POLYAMIDE (PA)
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	2

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		X
Nosebar Suitable		X
Powerturn Suitable		X
Slider Bed Suitable		X
Troughed Application Suitable		X
FDA / USDA Approved		X
Low Noise		X
Flame Retardant		X
Suitable for Metal Detector		X
Abrasion Resistant		X