



#77: XVT-2213 HABASIT (CM-14/40F)

Main Industry Segments: Cardboard converting, Paper manufacturing and processing; Paper manufacturing. Belt Applications: Folder-gluer belt, Processing belt. Special Features: Abrasion resistant, Adhesive-free joint, Constant coefficient of friction, Dimensionally stable, Forgiving in case of short term shock like overloads.

PLIES: 2 | TOP COVER: GREEN ROUGH STRUCTURE NBR | BOTTOM COVER: LIGHT GREEN NBR



[Request a Quote](#)

Tags: [Cardboard Converting](#), [Paper Processing](#)

TECHNICAL DATA

BELT THICKNESS:	4 mm	0.16"
PULLEY DIAMETER (MIN.):	50 mm	1.97"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:4.3	kg/m ²	0.881 lb/ft ²
PRODUCTION WIDTH:	1140 mm	44.88"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:	4 N/mm	23 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-20° to 65° C	-4° to 149° F

BELT CONSTRUCTION

TOP MATERIAL COVER:	NBR
SURFACE FINISH:	Rough Structure
PROPERTY:	
COLOR:	Light Green
BOTTOM COVER MATERIAL:	NBR
	Rough Structure
COLOR:	Yellow

BELT FABRIC

TOP PLY:	POLYAMIDE (PA)
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	2

BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable		✗
Troughed Application Suitable		✗
FDA / USDA Approved		✗
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector		✗
Abrasion Resistant		✗