





Request a Quote



Request a Sample

FECUNICAL DATA

## #03: FNV-10E 2-PLY WHITE MONO CONVEYOR BELT

The cover is FDA/USDA oil resistant nitrile/vinyl with special static dissipating polymer for dust control with non-adhesive surface, with good stain resistance. The carcass is constructed high tenacity yarns, with static dissipating fibers for dust control. Special weave construction promotes better tracking stability and minimum side shift inherent in most low friction belting. The special weave construction and the fact it is impregnated helps eliminate edge fraying (fuzz) minimizing contamination. Applications include: Pharmaceutical, Bakery, Vegetable Products, Meat & Poultry, Plastics, and Printing.

PLIES: 2 | TOP COVER: WHITE SMOOTH MODIFIED PVC | BOTTOM COVER: MONOFILAMENT FABRIC

**Tags:** Animal Fats, Bakery, Bulk Product Conveying, Disposable Diapers, Food Manufacturing, Food Processing, Fruits, General Conveying, Horticultural, Meat and Poultry, Nuts and Seeds, Plastics, Printing, Sanitary Towels, USDA / FDA, Vegetable Products

**BELT FABRIC** 

TECHNICAL DATA			
BELT THICKNESS:	2.54 mm		0.1"
PULLEY DIAMETER (MIN.):	38.1 mm		1.5"
PULLEY DIAMETER (MIN.) BACK FLEXING:	mm		п
BELT WEIGHT:	0.019 kg/m <sup>2</sup>	!	0.042 lb/ft²
PRODUCTION WIDTH:	21.33 mm		84"
BREAKING STRENGTH:			
TENSION FOR 1% ELONGATION:			105 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):			
OPERATING TEMPERATURE:	-7° to 82° C		20° to 180° F
BELT CONSTRUCTION			
TOP MATERIAL COVER:	Modified PVC		PVC
SURFACE FINISH:	Smooth		
PROPERTY:			
COLOR:		White	
BOTTOM COVER MATERIAL:		Monofila	ment Fabric
SURFACE FINISH:			
COLOR:			

TOP PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY				
INNER PLIES:					
BOTTOM PLY:	POLYESTER MONOFILAMENT WITH LATERAL STABILITY				
TOTAL NO. OF PLIES	2				
BELT CHARACTERISTICS					
	YES NO				
Dormonanthy Anti Ctati					

	YES	NO
Permanently Anti-Static	$\checkmark$	
Nosebar Suitable		×
Powerturn Suitable		×
Slider Bed Suitable	$\checkmark$	
Troughed Application Suitable		X
FDA / USDA Approved	$\checkmark$	
Low Noise		X
Flame Retardant		X
Suitable for Metal Detector		X
Abrasion Resistant		×