



## #06: PVC 120 WHITE CRESCENT TOP CONVEYOR BELT

Self-cleaning patters is ideal for incline conveying as well as creating tiny buckets for moving wet materials. Reversing belt drains product while conveying. Operates with out any bumping on return. FDA/UDSA Belt.

PLIES: 1 | TOP COVER: WHITE CRESCENT PVC | BOTTOM COVER: INTERWOVEN FRICTION


[Request a Quote](#)

[Request a Sample](#)

**Tags:** [Animal Fats](#), [Bakery](#), [Bulk Product Conveying](#), [Fish](#), [Food Manufacturing](#), [Food Processing](#), [Fruits](#), [General Conveying](#), [Horticultural](#), [Incline](#), [Material Handling](#), [Meat and Poultry](#), [Pharmaceutical](#), [Plastics](#), [Recycling](#), [Troughed Applications](#), [Unpackaged Food](#), [USDA / FDA](#), [Vegetable Products](#)

### TECHNICAL DATA

BELT THICKNESS:	6.35 mm	0.25"
PULLEY DIAMETER (MIN.):	63.5 mm	2.5"
PULLEY DIAMETER (MIN.)	mm	"
BACK FLEXING:		
BELT WEIGHT:	40.82 kg/m <sup>2</sup>	0.09 lb/ft <sup>2</sup>
PRODUCTION WIDTH:	mm	"
BREAKING STRENGTH:		
TENSION FOR 1% ELONGATION:		120 lbs/in
MAX. ADMISSIBLE BELT TENSION (EQUAL TO 1.8% STRETCH):		
OPERATING TEMPERATURE:	-7° to 82° C	20° to 180° F

### BELT CONSTRUCTION

TOP MATERIAL COVER:	PVC
SURFACE FINISH:	Crescent
PROPERTY:	
COLOR:	White
BOTTOM COVER MATERIAL:	Interwoven Friction
SURFACE FINISH:	
COLOR:	

### BELT FABRIC

TOP PLY:	UNIPLY INTERWOVEN
INNER PLIES:	
BOTTOM PLY:	
TOTAL NO. OF PLIES	1

### BELT CHARACTERISTICS

	YES	NO
Permanently Anti-Static		✗
Nosebar Suitable		✗
Powerturn Suitable		✗
Slider Bed Suitable	✓	
Troughed Application Suitable	✓	
FDA / USDA Approved	✓	
Low Noise		✗
Flame Retardant		✗
Suitable for Metal Detector	✓	
Abrasion Resistant		✗